

Key Features...

- Low cost
- High Performance
- Lightweight
- Alternative to Traditional Lead
- Waterproof
- Durable
- Easily Cut
- Easily Repaired
- No health and Safety Issues
- Long Life Guarantee

Technical Data

Colour	Grey		
Surface Finish	Dimpled		
Temp Resistance	-40°c / +90°c		
Min. Working Temp	+5°c		
Life Expectancy	Min. 20 Years		
Guarantee	15 Years		
Corrosion Resistance	Yes		

NO LEAD...

NO LEAD is a high performance low cost aluminium flashing suitable for use as an alternative to traditional lead in both flat and pitched roof applications.

NO LEAD is produced from sheet aluminium with a protective polyurethane coating on top and a polyisobutylene adhesive on the underside. Finished with a dimpled profile this unique construction ensures that **NO LEAD** is waterproof, durable and extremely malleable. The polyisobutylene adhesive ensures a strong permanent bond to all building materials without the need for a primer unless a surface is extremely unstable and forming a watertight joint requires no additional tape or sealant.

NO LEAD is extremely safe to use due to its light-weight construction and cutting and shaping is achieved with a knife or scissors that produce no sharp edges. Consequently installation is rapid and safe with no health and safety issues.

NO LEAD has a 15 year guarantee with a life expectancy in excess of 20 years.

<u>Product Data</u>			
Roll Width/mm	150	300	450
Roll Weight/Kilo	1.5	3	4.5
Roll Length/Metres	5	5	5
Rolls/Box	8	4	4
Rolls/Pallet	160	80	80

