SIMPLIPHI YOUR POWER WITH

AccESS to a fully integrated energy storage & management solution with OutBack Power equipment

- AccESS power security with safe, reliable, non-hazardous and efficient energy storage
- AccESS any power generation source with intelligent management
- AccESS your own power when and where you need it - inside or outside your home or business

STANDARD FEATURES Pre-programmed ESS for backup power, peak-shaving, and self-consumption of solar PV Internal transfer switch automatically disconnects from the grid during power outages and provides standby power for critical circuits Outdoor rated enclosure can be free-standing, or pad-mounted Advanced LFP batteries with up to a 10,000 cycle / 10-year warranty 98% round trip efficiency Remote monitoring by web browser or mobile device app No cobalt, thermal regulation, cooling, or risk of fire Extended operating temperature Solar MPPT for DC-coupled or off-grid installations

Automatic Generator control for additional standby power



Manufactured in the United States

SimpliPhi Power designs and manufactures efficient, non-toxic and enduring energy storage and management systems that utilize lithium ferro phosphate (LFP). Based in California, SimpliPhi combines non-hazardous LFP chemistry with its proprietary cell and battery architecture, power electronics, battery management system (BMS) and manufacturing methods to create safe, reliable, durable and highly scalable on-demand power solutions. Available for the residential, commercial, military and emergency response markets, SimpliPhi storage solutions have been rigorously tested and passed operational performance requirements by the U.S. Army and Marine Corps. Integral to all SimpliPhi solutions is a proprietary management system that further optimizes the life-cycle, round-trip efficiency rate, performance and durability of its batteries. SimpliPhi PHI 3.5 kWh 48V 60 Amp batteries are Certified to UL 1973 Standard.

Power. On Your Terms.™



SIMPLIPHI YOUR POWER WITH

AccESS to a fully integrated energy storage & management solution with OutBack Power equipment

APPLICATIONS

SIA (Standard Interconnection Agreement) customers: ESS allows for solar PV power to be self-consumed, while also providing a backup power source

NEM (Net Energy Metering) customers: add standby power and peak-shaving to a new or existing net-metered solar array

Off-grid customers: ESS with 8 kW Solar MPPT combines power generation and energy management in a single package

SPECIFICATIONS

General

29.5 x 76 x 20 in (w/feet), (75 x 193 x 51 cm) Dimensions (W x H x D)

Weight 600 lb (272.155 kg) (w/out batteries)

Enclosure Rating NEMA 3R Outdoor rated **Operating Temperature** -4 to 122 °F (-20 to 50 °C)

Mounting Free-standing or pad-mounted

Inverter/Charger

Radian GS8048A OutBack Power Application On / Off Grid

AC Connections 1 Grid Port, 1 Generator Port

AC Output1 120/240V AC, 60 Hz

Rated Power² 8 kW (7 kW²)

115A DC, 7.2 kW (30A AC @ 240V AC) Max Charge Rate

CEC Weighted Efficiency 92.50%

Battery

SimpliPhi Power PHI 3.5 kWh 48V DC 60 Amp (x4) UL 1973 Standard (ETL Certified) **UL** Rating

Rated kWh Capacity @ C/2 14 kWh Depth of Discharge³ up to 100%

Round Trip Efficiency 98%

Cycle Life 10,000+ (@ 80% DOD)

Warranty Period 10 years

Solar

OutBack Power Charge Controller FLEXmax 80 (x2) 8 kW Output Power (max) Charge Current (max) 160A DC 145V DC PV Array Voltage (max operating) 150V DC PV Array Voltage (max open circuit)

Other Features

OPTICS RE Internet Connected Monitor/Command

Automatic Generator Start Two wire generator only

System Display & Controller MATE3s

Notes: • 1. 240V AC standard; 120V AC on request.

- 2. When operating from battery, the maximum inverter power is half the battery capacity (kWh/2h).
- 3. Max operating conditions. Refer to Warranty for recommended conditions.
- Specifications are typical/nominal. Subject to change without notice.



Power. On Your Terms.™

3100 Camino Del Sol | Oxnard, CA 93030, USA | +1 (805) 640-6700 | SimpliPhiPower.com