

Declaration of Performance



Reference Number: RR/0009PM0 (Polyester, Mechanical, Oxidised)

Factory Production Control Certificate Number: 0836-CPR-13/F049

1. **Product Groups:**
Polyester Shed Felt

2. **Unique Product Names / Codes:**

Name	Code	Weight (kg)	Length (m)
5m Shed Felt Mineral (Green, Red)	P*10**5F	10kg	5m
10m Shed Felt Mineral (Green, Red)	P*20*10F	20kg	10m
20m Shed Felt Mineral (Green, Red)	P*40*20F	40kg	20m

3. **Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:**

Roof weatherproofing. Polyester based oxidised roofing membranes finished with a coloured medium slate mineral upper surface. For use as a roof covering on apex and pent roofed non habitable garden buildings and animal shelters, either mechanically fixed with clout headed nails and/or adhered with felt adhesive.

4. **Manufacturer:**
Rose Roofing Limited
1 Flass Lane
Cutsyke
Castleford
West Yorkshire
WF10 5JW
United Kingdom

5. **Authorised Representative:**
Not applicable

6. **System or systems of assessment and verification of constancy of performance of the construction product as set out in the Annex V of the CPR:**

System 2+

7. **Notified Body:**

The British Board of Agreement (BBA) performed an initial inspection of the manufacturing plant and factory production control, and performs continuous surveillance, assessment and evaluation of factory production control under system 2+ and issued a certificate of conformity of factory production control with reference to **BS EN 13707:2013** and **CPR 305/2011/EU**.

8. **Not applicable.**

9. Declared Performance:

Essential Characteristic	Specific Test ref.	Declared Performance	Harmonised Standard(hEN)
Watertightness	BS EN 1928 method a.	PASS	BS EN 13707:2013
Straightness	BS EN 1848-1	PASS	as above
Visible Defects	BS EN 1850-1	PASS	as above
External Fire Performance	BS EN 13501-5	F _{ROOF(t4)}	as above
Reaction to Fire	BS EN 13501-1	F	as above

For product variable essential characteristics such as length, mass per unit area, tensile strength and nail tear please refer to that individual product's data sheet.

10. The performance of the product identified in 1. and 2. above is in conformity with the declared performance stated in 9.

Signed by and on behalf of the manufacturer by:

Nick Sykes
Operations Director
Castleford, November 2013


