SMA REVENUE GRADE METER KIT





Accurate and versatile

- ANSI C12.20 revenue grade energy production monitoring provides a high level of accuracy
- Measures active, reactive and apparent power as well as grid voltage and frequency

Perfect alignment

- Designed for integration with Power+ Solution
- Ultra-compact DIN rail mounted meter kit mounts inside the Sunny Boy inverter

Plug-and-play

- Prewired and preassembled kit reduces installation time
- Quick and easy setup

SMA REVENUE GRADE METER KIT

Simple integration with extreme accuracy

SMA Revenue Grade Meter Kit is a revenue-grade energy meter designed for monitoring Sunny Boy inverter production with a 0.5% degree of accuracy. Its compact size and plug-and-play design allow it to be easily and quickly installed inside the Sunny Boy inverter. It collects a wide array of energy data which is either stored locally in the inverter or uploaded to the Sunny Portal allowing both system installers and owners to efficiently manage solar assets. It is designed to operate in unison with either the SMA Cellular LTE Modem Kit or the SMA RS485 Module.

Technical data	Revenue Grade Meter Kit
	RGM05KIT-US-10
General data	C114 CD 1 CD11C 1O
Compatible inverter models	SMA SBx.x-1SP-US-40 2.04.74.R or later
Compatible inverter firmware ANSI C12.20 measurement accuracy	2.04.74.K or later 0.5%
Operating voltage range	120 - 277 V AC
AC frequency range	45 - 65 Hz
Rated CT current	50 A
Measurement category	Category III - 300 V AC
Grids supported, single phase 2-wire	208 V WYE, 208 V Delta (no neutral), 240 V Split phase, 240 V Delta (no neutral)
Power consumption (typ.)	<2 VA
Dimensions (HxWxD)	$100 \times 100 \times 85 \text{ mm} / (3.94 \times 3.94 \times 3.35 \text{ in})$
Weight	0.4 kg (0.88 lb)
Temperature range (operating)	-25°C to +60°C (-13°F to +140°F)
Temperature range (standby)	-40°C to +60°C (-40°F to +140°F)
Relative humidity (non-condensing)	5 to 95%
Protection rating	NEMA 1 (IP40)
Mounting type	DIN rail (included in kit)
Warranty Supported communication interfaces	5 years Modbus RTU (SunSpec Certified)
Compliance	wiodous kilo (outropec Certifiled)
	IEC 61010-2-030:2010 (1st Edition), UL Std 61010.1:2012 (3rd Edition), Rev. July 15, 2015,
Safety	CAN/CSA C22.2 # 61010.1 (3rd Edition), Rev. July 15, 2015
EMC	IEC 61326-1 (2012) Ed2, IEC 61000-3-2, IEC 61000-3-3, IEC 61000-4-2,
Emissions	IEC 61000-4-3, IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-6, IEC 61000-4-8, IEC 61000-4-11 FCC Part 15 Class B / CISPR 11 Group1 Class B
Revenue metering	ANSI C12.20, Class 0.5
Communications	SunSpec Alliance certified
Other	RoHS Compliant
Meter type	Measurlogic DTS 307
Required accessories	
CELLMODKIT-US-10 or MD.485-US-40	Purchase separately

Type designation

RGM05KIT-US-10