

Declaration of Performance

Reference Number: RR/0009PMO

Factory Production Control Certificate Number: **UK 0836-CPR-13/F049**

1. Unique Product Names / Codes:

Name	Code	Weight (kg)	Length (m)
Premium			
5m Polyester Shed Felt	P*10**5F	12kg	5m
10m Polyester Shed Felt	P*20*10F	24kg	10m
15m Polyester Shed Felt	P*36*15F	36kg	15m
Trade			
8m Polyester Shed Felt	P*16**8F	16kg	8m
10m Polyester Shed Felt	P*20*10F	20kg	10m

2. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Roof waterproofing. A high performance polyester based oxidised/modified bitumen roofing membrane finished with a medium or fine grade green slate granule upper surface to aid UV protection. For use on apex and pent roofed non-habitable garden buildings and animal shelters, either mechanically fixed and/or adhered with felt adhesive.

3. Manufacturer: Rose Roofing Limited, 1 Flass Lane, Cutsyke, Castleford, West Yorkshire, WF10 5JW, United Kingdom

4. Authorised Representative: Not applicable

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in the Annex V of the CPR: System 2+

6. Notified Body:

The British Board of Agreement (BBA) performed an initial inspection of the manufacturing plant and factory production control, and performs continuous surveillance, assessment and evaluation of factory production control under system 2+ and issued a certificate of conformity of factory production control with reference to **BS EN 13707:2013** and **CPR 305/2011/EU**.

7. In Case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: Not applicable

8. Declared Performance:

Essential Characteristic	Specific Test ref.	Declared Performance	Harmonised Standard(hEN)
Watertightness	BS EN 1928 method a.	PASS	BS EN 13707:2013
Straightness	BS EN 1848-1	PASS	as above
Visible Defects	BS EN 1850-1	PASS	as above
External Fire Performance	BS EN 13501-1	FROOF (t4)	as above
Reaction to Fire	BS EN 13501-1	F	as above

For product variable essential characteristics such as length, mass per unit area, tensile strength and nail tear please refer to that individual product's data sheet.

9. The performance of the product identified in 1. and 2. above is in conformity with the declared performance stated in 9.

Signed by and on behalf of the manufacturer by:

Nick Sykes
Operations Director
Castleford, December 2021

