



INC-XANTO-Q110

☰ Faneurope code	INC-XANTO-Q110
▮ BARCODE	8031414930111
📖 DESCRIZIONE	Faretto da incasso con struttura in alluminio pressofuso antiriflesso con finitura in bianco satinato. Disponibile dalla forma quadrata o rotonda in diverse misure.
📖 DESCRIPTION	<i>Recessed spotlight with anti-glare die-cast aluminum structure with satin white finish. Available in square or round shape different sizes.</i>
👤 FAMIGLIA	XANTO
🏠 CATEGORIA	In.tec light INCASSI / RECESSED LAMPS
🏠 CATEGORY	In.tec light INCASSI / RECESSED LAMPS
📌 TIPOLOGIA	INCASSI
📌 TIPOLOGY	RECESSED
📏 MISUR PRODUCT	11 × 11 × 4,7 cm
💡 sorgente	2835 LED SMD
💡 Light_source	2835 LED SMD
💡 LAMPADINA INCLUSA/NON INCLUSA	led integrato
💡 BULD INCLUDED/ NOT INCLUDED	built-in led
💡 Lumen nominali	1250 lm
💡 Watt nominali	10W
🕒 Kwh/1000h	10.00
🕒 SWITCH-CCT_ITA	Selettore CCT all'installazione
🕒 SWITCH-CCT_ENG	CCT switch on installation
🌡️ KELVIN	CCT: 3000 - 4000 - 6500 K
📉 CRI	80
📐 BEAM-ANGLE	98°

ENERGY-CLASS	E
EPREL-NUMBER	2213987
LED-MODULE	M-XANTO-Q-10CCT-QL
N° MODULI	1
CATEGORIA_EPREL	PRODOTTO CONTENITORE
EPREL-CATEGORY	CONTAINING PRODUCT
SDCM	<6
CLASSE ISOLAMENTO	2
IP-DEGREE	IP20
IK-DEGREE	
DIMMER	NO
Volt	220/240V
Hertz	50/60hz
FORO-INCASSO	Foro: 100 × 100 mm
HOLE-INFORMATION	Cut out: 100 × 100 mm
MaterialeStruttura	Alluminio
StructureMaterial	Aluminum
MaterialeDiffusore	Alluminio pressofuso
DiffuserMaterial	Die-cast aluminum
Dissipazione	Alluminio Aluminum
colore	Bianco
Colour	White
ColoreDiffusore	Bianco
DiffuserColour	White
InfoDriverITA	LIFUD driver
DriverinfoENG	LIFUD driver
Hz	
BATTERY-Amh	
Life/H	
Power-Wh	
H-CHARGE	
Garanzia	3 Anni
Warranty	3 years
Nomenclatura doganale/CustomCode	94051140
RemoteControl_ITA	
RemoteControl_ENG	
Dedicated_App	