

Declaration of Performance

Reference Number: RR/0002GMO

Factory Production Control Certificate Number: **UK 0836-CPR-13/F049**

1. Unique Product Names / Codes:

Name	Code	Weight (kg)	Length (m)
Standard			
5m Shed Felt Mineral	G*10**5F	10kg	5m
10m Shed Felt Mineral	G*20*10F	20kg	10m
20m Shed Felt Mineral	G*40*20F	40kg	20m
Trade			
8m Shed Felt Mineral	G144**8F	14.4kg	8m
10m Shed Felt Mineral	G*18*10F	18kg	10m

2. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Roof weatherproofing. Glass fibre based oxidised roofing membranes finished with a coloured medium slate mineral upper surface. For use as a roof covering on apex and pent roofed non habitable garden buildings and animal shelters, either mechanically fixed and/or adhered with felt adhesive.

3. **Manufacturer:** Rose Roofing Limited, 1 Flass Lane, Cutsyke, Castleford, West Yorkshire, WF10 5JW, United Kingdom

4. **Authorised Representative:** Not applicable

5. **System or systems of assessment and verification of constancy of performance of the construction product as set out in the Annex V of the CPR:** System 2+

6. Notified Body:

The British Board of Agreement (BBA) performed an initial inspection of the manufacturing plant and factory production control, and performs continuous surveillance, assessment and evaluation of factory production control under system 2+ and issued a certificate of conformity of factory production control with reference to **BS EN 13707:2013** and **CPR 305/2011/EU**.

7. **In Case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:** Not applicable

8. Declared Performance:

Essential Characteristic	Specific Test ref.	Declared Performance	Harmonised Standard(hEN)
Watertightness	BS EN 1928 method a.	PASS	BS EN 13707:2013
Straightness	BS EN 1848-1	PASS	as above
Visible Defects	BS EN 1850-1	PASS	as above
External Fire Performance	BS EN 13501-5	FROOF(t4)	as above
Reaction to Fire	BS EN 13501-1	F	as above

For product variable essential characteristics such as length, mass per unit area, tensile strength and nail tear please refer to that individual product's data sheet. Above results based on test of lightest weight product of 1.8kg / m².

9. **The performance of the product identified in 1. and 2. above is in conformity with the declared performance stated in 9.**

Signed by and on behalf of the manufacturer by:

Nick Sykes
Operations Director
Castleford, December 2021

