SIMPLIPHI YOUR POWER WITH **EPHI 3.2** HIGH OUTPUT BATTERY



The PHI 3.2[™] kWh 160 Amp deep-cycle Lithium Ferro Phosphate (LFP) battery is optimized with proprietary cell architecture, power electronics, BMS and assembly methods. It is modular, lightweight and scalable for installations that range from kWh to MWh. Provides power security and seamless integration of renewable and traditional sources of energy in conjunction with or independent of the grid: net zero, peak shaving, emergency back-up, portable and mobile.

- 24V LFP batteries with proprietary architecture and Battery Management System (BMS)—do not require ventilation, cooling or thermal regulation
- Compatible with all industry standard inverter/charge controllers
- · Drop in replacement for lead acid
- LFP is the safest, most environmentally benign Lithium Ion chemistry available—no cobalt, risk of thermal runaway or fire
- No AC or toxic liquid cooling—negligible parasitic drain —long cycle life
- Non-toxic and non-hazardous recyclable materials

PHI 3.2 ™	24V	
DC Voltages - Nominal	25.6 V	
Amp Hours	126 Ah	
Rated kWh Capacity @ C/2	3.2 kWh Hours	8
Max Peak Current	160 Amps / 5 minutes	
Max Current	140 Amps / 15 minutes	
Continuous Current	110 Amps	
Max Charge Current	70 Amps	
DC Voltage Range ¹	20 to 28.8	
Depth of Discharge ¹	up to 100%	
Operating Efficiency	98%	-
Operating Temp ¹	-4° to 140°F (-20° to 60°C)	
Charge Temp ¹	32° to 120°F (0° to 49°C)	
Self-Discharge Rate	<1% loss per month	
Cyle Life	5,000+ (@ 80% DoD)	
Memory Effect	None	
Warranty Period	5 Years	
Dimensions	13.5 x 14 x 8 inches / 0.88 cu ft (34.29	x 35.
Weight	75.5 lbs (34.8 kg)	

- 1. Max operating conditions. Refer to warranty for recommended conditions.
- All specifications listed are typical/nominal and subject to change without notice.
- UN 3480, Lithium ion batteries, 9, II
- UL, CE, UN/DOT and RoHS compliant components
- · Designed and built in California, USA





