

Declaration of Performance

Reference Number: RR/0006GPO

Factory Production Control Certificate Number: **UK 0836-CPR-13/F049**

1. Unique Product Names / Codes:

Name	Code	Weight (kg)	Length (m)
Glass Bonding Sand (3B)	GL36S20F	36kg	20m
Glass Perforated Sand (3H)	GL34S20F	34kg	20m
Glass Perforated Green Mineral (3G)	GL26G10F	26kg	10m
Glass Capsheet Mineral (3E)	GL28G10F	28kg	10m

2. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Roof waterproofing. Glass based oxidised bitumen roofing membranes finished with a coloured coarse slate mineral or sand upper surface. For use as underlays, intermediate layers, and capsheets as part of a traditional pour and roll built up roof system for both domestic and commercial properties. Adhered with hot poured bitumen.

3. Manufacturer: Rose Roofing Limited, 1 Flass Lane, Cutsyke, Castleford, West Yorkshire, WF10 5JW, United Kingdom

4. Authorised Representative: Not applicable

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in the Annex V of the CPR: System 2+

6. Notified Body:

The British Board of Agreement (BBA) performed an initial inspection of the manufacturing plant and factory production control, and performs continuous surveillance, assessment and evaluation of factory production control under system 2+ and issued a certificate of conformity of factory production control with reference to **BS EN 13707:2013** and **CPR 305/2011/EU**.

7. In Case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: Not applicable

8. Declared Performance:

Essential Characteristic	Specific Test ref.	Declared Performance	Harmonised Standard(hEN)
Watertightness	BS EN 1928 method a.	PASS	BS EN 13707:2013
Straightness	BS EN 1848-1	PASS	as above
Visible Defects	BS EN 1850-1	PASS	as above
External Fire Performance	BS EN 13501-5	FROOF(t4)	as above
Reaction to Fire	BS EN 13501-1	F	as above

For product variable essential characteristics such as length, mass per unit area, tensile strength and nail tear please refer to that individual product's data sheet.

9. The performance of the product identified in 1. and 2. above is in conformity with the declared performance stated in 9.

Signed by and on behalf of the manufacturer by:

Nick Sykes
Operations Director
Castleford, December 2021

